

Vandal Resistant IR Dome Camera

DESCRIPTION

Designed for areas that are prone to attack, the DSIRHRV is enclosed in a vandal resistant and weatherproof housing. The robust design of the DSIRHRV makes it a highly visible camera that can act as a deterrent in hostile environments.

This high-resolution ball dome comes complete with 24 in-built IR LEDs and CDS sensor. Amongst a wide array of functions, the DSIRHRV features an external zoom/focal adjustment for ease of setup.




DSIRHRV/S - Silver Casing

KEY FEATURES

■ CCD	1/3"
■ Resolution Colour	540 Lines
■ Resolution Mono	625 Lines
■ Sensitivity Colour	0.1 Lux
■ Sensitivity Mono	0 Lux
■ Number of Infra Red LEDs	24
■ IR Range	30m
■ Lens Size	4-9mm Varifocal
■ Voltage	12V DC
■ Power Consumption	370mA
■ Dimensions	120(Ø)x96(H)mm
■ Weight	Approx. 600g

Other Features

- True Day Night
- Auto White Balance
- Auto Gain Control
- Back Light Compensation
- Tri-Axis Gimbal



DSIRHRV

Vandal Resistant IR Dome Camera

TECHNICAL SPECIFICATION

Image Pick-up Device	1/3"
Effective Picture Elements	752x582
Horizontal Resolution	540 TV Lines
Minimum Illumination	0.1Lux (CDS ON : 0.000Lux)
S/N Ratio	45dB
Auto Electronic Shutter	1/50s~1/100,000
Iris Control	Auto
Gamma Characteristic	0.45
Lens mount	4~9mm Vari Focal Lens(F=1.6)
Backlight compensation	ON
AGC	Auto
Synchronous System	Negative sync, Internal
Video Output	1Vp-p Composite Video/75 Ohms
Power Supply	DC 12V / 140mA (CDS ON : 400mA Max)
Operating Temp	-20°C to 50°C
Dimensions	120(W)mmx96(D)mm
Weight	Approx 600g