

VC564K / VC264K

Body Camera c/w lens & bracket



The VC564K and VC264K camera packages incorporate the very latest CCD technology that offers high picture quality and sensitivity. Available in 420 TVL (Monochrome) and 380 TVL (Colour) and a minimum illumination of 0.1 Lux (Monochrome) and 2.0 Lux (Colour) both cameras are suitable for internal applications and come complete with a 3.6mm fixed iris lens and wall mount bracket.

VC564K

VC264K

■ CCD	1/3"	1/3"
■ Resolution	420 Lines	380 Lines
■ Sensitivity	0.1 Lux	2.0 Lux
■ Lens Mount	C/CS	C/CS
■ Lens	EI / AI/ DD	EI / AI/ DD
■ Voltage	12V DC	12V DC
■ Power Consumption	110mA	110mA
■ Dimensions	40x40x53mm	40x40x53mm
■ Weight	Approx. 150g	Approx. 150g

Model	VC564K	VC264K
Type	Monochrome	Colour
Sensor	1/3"	
Power	12V DC	
Pixels	500 x 582	
Resolution	420TVL	380TVL
Scanning System	2 : 1 Interface	
Sensitivity	0.1 Lux	2.0 Lux @ F2.0
S/N Ratio	>48dB	
Gamma Correction	0.45	No
Gain Control	Auto	
Exposure	AE On/Off Selectable	
Video Output	1.0 p-p 750 Ohm Load	
Power Consumption	150mA	
Operating Temperature	-10°C to 50°C	
Lens Mount Type	C /CS	
Power Supply	PCAM05 (not included)	

Recommended Power Supply



PCAM05

Plug in PSU 12V DC 400mA with flying leads. Continuous rating.



Digital CCTV Limited
The Old School, Woughton Park, Milton Keynes
MK6 3AP UK 01908 239239 sales@digitalcctv.com